



STAKE MARKS AVAILABLE

DOUBLE OR SINGLE NOTCHED CORNERS ON HEX INDICATE HEAT TREATED TO RC 26-34

Size	Continental-Aero Part Number *See Note	Thread †See Note	Standard Container Quantity	Weight Lbs./C (Steel)	A Height **See Note	B Across Flats	C (Ref) Across Corners	D (Ref) Wrench Pad
1/4	5XN1610-040	1/4-20	6000	0.90	.313	.439-.430	.482	.225
	5XN1610-048	1/4-28						
5/16	5XN1610-058	5/16-18	4000	1.20	.344	.502-.492	.552	.250
	5XN1610-054	5/16-24						
3/8	5XN1610-066	3/8-16	2500	1.80	.453	.564-.553	.622	.335
	5XN1610-064	3/8-24						
7/16	5XN1610-074	7/16-14	2000	2.30	.453	.627-.616	.694	.324
	5XN1610-070	7/16-20						
1/2	5XN1610-083	1/2-13	1000	4.30	.594	.752-.741	.837	.464
	5XN1610-080	1/2-20						
9/16	5XN1610-092	9/16-12	700	7.10	.641	.877-.865	.978	.469
	5XN1610-098	9/16-18						
5/8	5XN1610-101	5/8-11	550	8.30	.750	.940-.928	1.051	.593
	5XN1610-108	5/8-18						
3/4	5XN1610-120	3/4-10	350	12.00	.875	1.064-1.052	1.191	.742
	5XN1610-126	3/4-16						
7/8	5XN1610-149	7/8-9	250	19.00	.984	1.252-1.239	1.403	.790
	5XN1610-144	7/8-14						
1	5XN1610-168	1-8	150	27.00	1.047	1.440-1.427	1.615	.825
	5XN1610-162	1-12						
	5XN1610-164	1-14						
1 1/8	5XN1610-187	1 1/8-7	100	41.00	1.172	1.627-1.614	1.826	.930
	5XN1610-182	1 1/8-12						
1 1/4	5XN1610-207	1 1/4-7	92	58.00	1.391	1.814-1.801	2.038	1.125
	5XN1610-202	1 1/4-12						
1 3/8	5XN1610-226	1 3/8-6	72	77.00	1.578	2.008-1.973	2.232	1.282
	5XN1610-222	1 3/8-12						
1 1/2	5XN1610-246	1 1/2-6	60	100.00	1.609	2.197-2.159	2.416	1.313
	5XN1610-242	1 1/2-12						

Locking Insert: Purple nylon (250°F max. performance) white and staked available.

* **Note:** See page 2 for parts nomenclature; substitute digits for material and finish in place of "xx" in part numbers above.

** **Note:** TOLERANCES — 1/4 through 3/8: ±.015; 1" through 1 1/2: ±.031.

† **Note:** Other thread sizes are available from stock or on application.

Material—Steel (AISI C1137 or equivalent). Heat-Treated Rockwell C 26-34.