



**STAKE MARKS  
AVAILABLE**

Size	Continental-Aero Part Number *See Note	Thread †See Note	Standard Container Quantity	Weight Lbs./C (Steel)	A Height **See Note	B Across Flats	C (Ref) Across Corners	D (Ref) Wrench Pad
1/4	xxNE040	1/4-20	6000	0.90	.313	.439-.430	.482	.225
	xxNE048	1/4-28						
5/16	xxNE058	5/16-18	4000	1.20	.344	.502-.492	.552	.250
	xxNE054	5/16-24						
3/8	xxNE066	3/8-16	2500	1.80	.453	.564-.553	.622	.335
	xxNE064	3/8-24						
7/16	xxNE074	7/16-14	2000	2.30	.453	.627-.616	.698	.324
	xxNE070	7/16-20						
1/2	xxNE083	1/2-13	1000	4.30	.594	.752-.741	.837	.464
	xxNE080	1/2-20						
5/8	xxNE092	5/8-12	700	7.10	.641	.877-.865	.978	.469
	xxNE098	5/8-18						
3/4	xxNE101	3/4-11	550	8.30	.750	.940-.928	1.051	.593
	xxNE108	3/4-18						
7/8	xxNE120	7/8-10	350	12.00	.875	1.064-1.052	1.191	.742
	xxNE126	7/8-16						
1	xxNE149	1-9	250	19.00	.984	1.252-1.239	1.403	.790
	xxNE144	1-14						
1 1/8	xxNE168	1-8	150	27.00	1.047	1.440-1.427	1.615	.825
	xxNE162	1-12						
	xxNE164	1-14						
1 1/4	xxNE187	1 1/8-7	100	41.00	1.172	1.627-1.614	1.826	.930
	xxNE182	1 1/8-12						
1 1/2	xxNE207	1 1/4-7	92	58.00	1.391	1.814-1.801	2.038	1.125
	xxNE202	1 1/4-12						
1 3/4	xxNE226	1 3/8-6	72	77.00	1.578	2.008-1.973	2.232	1.282
	xxNE222	1 3/8-12						
2	xxNE246	1 1/2-6	60	100.00	1.609	2.197-2.159	2.416	1.313
	xxNE242	1 1/2-12						

**Locking Insert:** Purple nylon (250°F max. performance) white and staked available.

\* **Note:** See page 2 for parts nomenclature; substitute digits for material and finish in place of "xx" in part numbers above.

\*\* **Note:** TOLERANCES — 1/4 through 3/8: ±.015; 1" through 1 1/2 ±.031.

† **Note:** Other thread sizes are available from stock or on application.