





The bright purple nylon insert identifies Tork Lok Nuts and denotes precision manufacture from the finest materials, to assure top product performance. "Look for the Royal Purple Insert!"



NU8 (NU1610) SERIES



STAKE MARKS AVAILABLE

DOUBLE OR SINGLE NOTCHED CORNERS ON HEX INDICATE HEAT TREATED TO RC 26-34

Size	Continental-Aero Part Number *See Note	Thread †See Note	Weight Lbs./C (Steel)	A Height **See Note	B Across Flats	C (Ref) Across Corners	D (Ref) Wrench Pad
1	5XNU1610-168	1-8	48.0	1.281	1.632-1.602	1.796	1.000
	5XNU1610-164	1-14					
1¼	5XNU1610-207	1¼-7	92.0	1.641	2.008-1.973	2.209	1.250
	5XNU1610-202	1¼-12					
	5XNU1610-208	1¼-8					
1¾	5XNU1610-226	1¾-6	120.0	1.797	2.197-2.159	2.416	1.376
	5XNU1610-222	1¾-12					
	5XNU1610-228	1¾-8					
1½	5XNU1610-246	1½-6	150.0	1.922	2.384-2.344	2.622	1.413
	5XNU1610-242	1½-12					
	5XNU1610-248	1½-8					
1⅝	5XNU1610-265	1⅝-5	185.0	2.141	2.572-2.530	2.886	1.637
	5XNU1610-262	1⅝-12					
1¾	5XNU1610-285	1¾-5	240.0	2.313	2.762-2.715	3.035	1.830
	5XNU1610-282	1¾-12					
	5XNU1610-288	1¾-8					
1⅞	5XNU1610-305	1⅞-5	270.0	2.359	2.950-2.901	3.242	1.875
	5XNU1610-302	1⅞-12					
2	5XNU1610-324	2-4½	310.0	2.406	3.137-3.086	3.449	1.750
	5XNU1610-322	2-12					
	5XNU1610-328	2-8					
2¼	5XNU1610-364	2¼-4½	450.0	2.813	3.514-3.457	3.862	2.063
	5XNU1610-362	2¼-12					
	5XNU1610-368	2¼-8					
2½	5XNU1610-404	2½-4	682.0	3.141	4.015-3.875	4.618	2.475
	5XNU1610-402	2½-12					
	5XNU1610-408	2½-8					
2¾	5XNU1610-444	2¾-4	530.0	3.141	4.015-3.875	4.618	2.350
	5XNU1610-442	2¾-12					
	5XNU1610-448	2¾-8					
3	5XNU1610-484	3-4	1000.0	3.641	4.640-4.500	5.102	2.750
	5XNU1610-482	3-12					

Locking Insert: Purple nylon (250°F max. performance) white and staked available.

* **Note:** See page 2 for parts nomenclature; substitute digits for material and finish in place of "xx" in part numbers above.

** **Note:** TOLERANCES — 1" through 1½: ±.031; 1⅝" and over ±.063.

† **Note:** Other thread sizes are available from stock or on application.

Material—Steel (AISI C1137 or equivalent). Heat-Treated Rockwell C 26-34.