



## AERO-FLEX Locknuts - *Now available*

*Call your account manager or email [sales@continental-aero.com](mailto:sales@continental-aero.com)*

Item	Plain finish Part #	Cad / Wax Part #	Size	Thread Fit	Proof Load Lbs	Across Flats Max	Across Flats Min	Across Corners Ref	Thickness Max	Hex Height Min	Unit Weight lbs/m
Light Hex Full Height	29AFLF0420	L22AFLF0420	1/4-20	UNC-2B	5,730	.439	.430	.491	.290	.122	7.4
	29AFLF0428	L22AFLF0428	1/4-28	UNF-3B	6,550	.439	.430	.491	.320	.135	7.4
	29AFLF0518	L22AFLF0518	5/16-18	UNC-2B	9,600	.502	.492	.561	.353	.150	11.6
	29AFLF0524	L22AFLF0524	5/16-24	UNF-3B	9,950	.502	.492	.561	.353	.150	11.6
	29AFLF0616	L22AFLF0616	3/8-16	UNC-2B	13,800	.564	.553	.631	.492	.210	17.8
	29AFLF0624	L22AFLF0624	3/8-24	UNF-3B	14,500	.564	.553	.631	.492	.210	17.8
	29AFLF0813	L22AFLF0813	1/2-13	UNC-2B	22,000	.752	.741	.846	.602	.285	42.1
	29AFLF0820	L22AFLF0820	1/2-20	UNF-3B	23,800	.752	.741	.846	.602	.285	42.1
	29AFLF1011	L22AFLF1011	5/8-11	UNC-2B	34,000	.940	.928	1.059	.759	.410	84.4
	29AFLF1018	L22AFLF1018	5/8-18	UNF-3B	38,400	.940	.928	1.059	.759	.410	84.4
	29AFLF1210	L22AFLF1210	3/4-10	UNC-2B	50,000	1.064	1.052	1.200	.884	.505	122.7
	29AFLF1216	L22AFLF1216	3/4-16	UNF-3B	52,300	1.064	1.052	1.200	.884	.505	122.7

# CONTINENTAL-AERO



**AERO-FLEX Locknuts – All Metal Prevailing Torque  
Higher Temperature use than Nylon Inserts  
Stronger hold than distorted thread style  
Light Hex – Full Height and Thin Height Pattern**

Item	Plain finish Part #	Cad / Wax Part #	Size	Thread Fit	Proof Load Lbs	Across Flats Max	Across Flats Min	Across Corners Ref	Thickness Max	Hex Height Min	Unit Weight lbs/m
Light Hex Thin Height	29AFLT0420	L22AFLT0420	1/4-20	UNC-2B	4,450	.439	.430	.491	.219	.075	5.5
	29AFLT0428	L22AFLT0428	1/4-28	UNF-3B	5,090	.439	.430	.491	.219	.075	5.5
	29AFLT0616	L22AFLT0616	3/8-16	UNC-2B	7,360	.564	.553	.631	.282	.108	10.8
	29AFLT0624	L22AFLT0624	3/8-24	UNF-3B	8,340	.564	.553	.631	.282	.108	10.8
	29AFLT0813	L22AFLT0813	1/2-13	UNC-2B	11,400	.752	.741	.846	.328	.121	22.4
	29AFLT0820	L22AFLT0820	1/2-20	UNF-3B	12,800	.752	.741	.846	.328	.121	22.4
	29AFLT1011	L22AFLT1011	5/8-11	UNC-2B	18,100	.940	.928	1.059	.399	.147	44
	29AFLT1018	L22AFLT1018	5/8-18	UNF-3B	20,500	.940	.928	1.059	.399	.147	44
	29AFLT1210	L22AFLT1210	3/4-10	UNC-2B	26,800	1.064	1.052	1.200	.415	.155	51.5
	29AFLT1216	L22AFLT1216	3/4-16	UNF-3B	29,800	1.064	1.052	1.200	.415	.155	51.5